


OPTIONS AND ACCESORIES

RC Modules for Pulse shape forming

150 pF / 2'000 Ω (ISO 10605)	No. 4700531
330 pF / 2'000 Ω (ISO 10605)	No. 4700532
330 pF / 330 Ω (ISO 10605)	No. 4700618
100 pF / 1'500 Ω	No. 4700622
150 pF / 150 Ω	No. 4700620
500 pF / 500 Ω	No. 4700619
500 pF / 5'000 Ω	No. 4700621
50 pF .. 1 nF / 50 Ω .. 5'000 Ω (custom)	No. 4700633



Tips

30kV AD Tip	Discharge tip 30 mm diameter for improved air discharge testing up to 30 kV	No. 4700526
Fast Rise Time Tip	Fast rise Tip Reduces the rise time of the ESD-pulse to 0.3 ns for reliability	No. 4700527

Software

Package of fibre optical RS 232 interface and control & report 2490216 software	No. 2490214
---	-------------



Others

ONYX Balancer	Balancing tool with mounting system up to 2.3 kg	No. 4781300
ESD Verification Set	For wave shape verification according to IEC/EN 61000-4-2	No. 4700480
HCP	Horizontal coupling plane 1.6 m x 0.8 m for indirect application of the ESD. Includes cable with 2 integrated 470 kΩ HV-resistors	No. 4700480
VCP	Vertical coupling plane 0.5 m x 0.5 m, for indirect application of the ESD. Includes cable with 2 integrated 470 kΩ HV-Resistors	No. 4700480
Test Table	Table 160 x 80 cm, made of wood without any metallic parts, as required by IEC 61000-4-2	No. 2495581
Remote Control IAC	Package of fibre optical RS 232 interface and control & report software	No. 2496871
AC Mains Adapter	Power supply replaces the rechargeable battery pack for 2490214 continuous testing	No. 2490214
Acc. Calibration	Accredited calibration according to ISO/IEC 17025 Calibration requirements	No. 2499981



SOFTWARE

Windows based software optional to help making tests more reliable and reproducible.

Benefits:

- Windows XP, Windows Vista and Windows 7 compatibility
- Support of USB and optical USB interfaces
- Easy-to-use and intuitive creator for test plans and test procedures
- Enhanced and highly flexible reporting capabilities
- Up-to-date design and navigation

